


DPJ 端式接头 DPJ End Type Connector

- 本体材料: 锌合金镀锌; 盖封螺母: 锌合金镀铬
- 护圈: TPE; 密封圈: 改性橡胶; 软管护口: 镀锌铁皮
- 温度: -40°C ~ 100°C
- 防护等级: 最高可达IP65
- DPJ接头适用于JS、JSH、JSB软管的连接, JSG软管需接DPJW接头。
订货请注明软管规格及螺纹尺寸, 例DPJ-15-G1/2", 一端φ15软管, 另一端G1/2"外螺纹。



DPJ型端接头(六角螺母)
DPJ end type connector
(hexagon nut)



- Body Material: Zinc alloy galvanizing; Cover nut: zinc alloy Chrome plating
- Guarding: TPE; Seal: modified rubber; Ferrule: galvanized steel
- Temperature Range: Min -40 °C, Max 100 °C
- Protection Level: Up to IP65
- DPJ connector fits with JS, JSH and JSB conduits, JSG conduit fits with DPJW connector, please inform the dimension of the conduit and the thread such as DPJ-15-G1/2", one end φ15 conduit and the other end G1/2" outer



锁紧螺母
lock nut



密封圈
seal



衬套
bushing



主体
body



软管护口
ferrule



软管护圈
guarding



盖封螺母
cover lock nut

DPJ 端式接头部分推荐螺纹尺寸 The Recommended Dimension Of The Connector

适配软管尺寸 for conduit size 公制Metric	英制螺纹 English thread	螺纹长度 GL	公制螺纹 Metric thread	螺纹长度 GL	德制螺纹 PG	螺纹长度 GL	扳手尺寸 Wrench size	包装单位 packet units
Ø6	G1/4"	7	M12 / M14	7	PG7	8.5	18/16	100
Ø8	G3/8"	12	M14 / M16	8	PG9	8.5	24/22	50
Ø10	G3/8"	7	M16	8	PG9	9.5/10.5	24/22	50
Ø12	G3/8"	10	M18 / M20	10	PG11/ PG13.5	11/11	26	50
Ø15	G1/2"	12	M20 / M22 / M24	10	PG13.5 / PG16	11.5	30	50
Ø20	G3/4"	12	M25 / M27 / M30	12	PG21	13	35	25
Ø25	G1"	14	M32 / M33 / M36	12	PG29	13	43	20
Ø32	G1 1/4"	14	M36 / M40 / M42 / M48	14	PG29	13	52	10
Ø38	G1 1/2"	16	M48 / M50	14	PG36 / PG42	17/16	60	10
Ø51	G2"	16	M60 / M63 / M64 / M72	15	PG48	19	75	5
Ø64	G2 1/2"		M76	20			89/87	2
Ø75	G3"		M88	22			102/97	2
Ø100	G4"		M114	28			133/128	2
Ø125	G5"		M140	29			158	2
Ø150	G6"		M164	29			183	2