


## WQG1 快速软管接头 Quick Screw Connector

- 材料: 尼龙
- 颜色: 深灰色(RAL 7037),黑色(RAL 9005),
- 温度:-40°C~100°C, 短时达到120°C
- 阻燃等级:V2(UL94)
- 防护等级:IP66
- 阻燃性能:自熄灭性好, 不含卤素、磷、镉,通过RoHS测试
- 适配:除重载型WYK软管外的所有软管

- Material: Polyamide
- Color: grey (RAL 7037), black (RAL 9005)
- Temperature Range: Min-40°C Max100°C, Short-term120°C
- Flame-retardant: V2(UL94)
- Protection degree: IP66
- Flame-retardant: Self-extinguishing, free of halogen,phosphor and cadmium, passed RoHS.
- Fit with: All tubing except Overload type WYK tubing



UL证书号: E317026



## WQG1-M 公制螺纹 Metric Thread

灰色编号 article no. grey	黑色编号 article no. black	螺纹规格 Thread Dimension	适配软管AD Fits to tubing size	螺纹长度C Thread length	孔径 φ I mm	外径 φ B mm	长度D Total length mm	扳手尺寸 SW wrench size	包装单位 Packet units
WQG1-M10G/AD10.0	WQG1-M10B/AD10.0	M10×1.0	AD10.0	12	6	17	35	15.5	50
WQG1-M12G/AD10.0	WQG1-M12B/AD10.0	M12×1.5	AD10.0	12	7	17	35	15.5	50
WQG1-M12G/AD13.0	WQG1-M12B/AD13.0	M12×1.5	AD13.0	12	7	20	37	18	50
WQG1-M16G/AD13.0	WQG1-M16B/AD13.0	M16×1.5	AD13.0	12	10	20	37	18	50
WQG1-M16G/AD15.8	WQG1-M16B/AD15.8	M16×1.5	AD15.8	12	11.5	23	39.5	21	50
WQG1-M18G/AD15.8	WQG1-M18B/AD15.8	M18×1.5	AD15.8	12	12	23	39.5	21	50
WQG1-M20G/AD15.8	WQG1-M20B/AD15.8	M20×1.5	AD15.8	12	12	23	39.5	21	50
WQG1-M20G/AD18.5	WQG1-M20B/AD18.5	M20×1.5	AD18.5	13	14.5	26	42	24	50
WQG1-M20G/AD21.2	WQG1-M20B/AD21.2	M20×1.5	AD21.2	13	15.5	29.5	45	27	50
WQG1-M22G/AD21.2	WQG1-M22B/AD21.2	M22×1.5	AD21.2	13	17	29.5	45	27	50
WQG1-M24G/AD21.2	WQG1-M24B/AD21.2	M24×1.5	AD21.2	13	17	29.5	45	27	50
WQG1-M25G/AD21.2	WQG1-M25B/AD21.2	M25×1.5	AD21.2	13	17	29.5	45	27	50
WQG1-M25G/AD25.5	WQG1-M25B/AD25.5	M25×1.5	AD25.5	13	20.5	34	46.5	31	25
WQG1-M25G/AD28.5	WQG1-M25B/AD28.5	M25×1.5	AD28.5	13	20.5	37	47	34	25
WQG1-M27G/AD28.5	WQG1-M27B/AD28.5	M27×2.0	AD28.5	13	22.5	37	47	34	25
WQG1-M30G/AD28.5	WQG1-M30B/AD28.5	M30×2.0	AD28.5	13	23.5	37	47	34	25
WQG1-M32G/AD28.5	WQG1-M32B/AD28.5	M32×1.5	AD28.5	13	23.5	37	47	34	25
WQG1-M32G/AD31.5	WQG1-M32B/AD31.5	M32×1.5	AD31.5	15	26	41	51	37	25
WQG1-M32G/AD34.5	WQG1-M32B/AD34.5	M32×1.5	AD34.5	15	26	44	51	40	25
WQG1-M33G/AD34.5	WQG1-M33B/AD34.5	M33×2.0	AD34.5	15	26	44	51	40	25
WQG1-M36G/AD34.5	WQG1-M36B/AD34.5	M36×2.0	AD34.5	15	30	44	51	40	25
WQG1-M40G/AD34.5	WQG1-M40B/AD34.5	M40×1.5	AD34.5	15	28.5	44	51	40	25
WQG1-M40G/AD42.5	WQG1-M40B/AD42.5	M40×1.5	AD42.5	15	33	52	54	50	10
WQG1-M42G/AD42.5	WQG1-M42B/AD42.5	M42×2.0	AD42.5	15	35	52	54	50	10
WQG1-M48G/AD42.5	WQG1-M48B/AD42.5	M48×2.0	AD42.5	15	36.5	52	54	50	10
WQG1-M50G/AD42.5	WQG1-M50B/AD42.5	M50×1.5	AD42.5	15	36.5	52	54	50	10
WQG1-M50G/AD54.5	WQG1-M50B/AD54.5	M50×1.5	AD54.5	16	43	64	55	60	5
WQG1-M56G/AD54.5	WQG1-M56B/AD54.5	M56×2.0	AD54.5	16	48	64	55	60	5
WQG1-M60G/AD54.5	WQG1-M60B/AD54.5	M60×2.0	AD54.5	16	48	64	55	60	5
WQG1-M63G/AD54.5	WQG1-M63B/AD54.5	M63×1.5	AD54.5	16	48	64	55	60	5
WQG1-M64G/AD54.5	WQG1-M64B/AD54.5	M64×2.0	AD54.5	16	48	64	55	60	5